



Regent®

User Guide



Britax

Safety Warnings	2
Safety Information	4
Child Seat Features	8
Vehicle Compatability	10
Vehicle Safety Belts.....	10
Vehicle Seating Positions	11
Installation for Children 22– 40 lbs.	12
LATCH – Long Route	12
Lap-Shoulder Belt – Long Route	15
Lap-Belt – Long Route	17
Installation for Children 40 – 80 lbs.	19
LATCH – Short Route	19
Lap-Shoulder Belt – Short Route	22
Lap-Belt – Short Route	24
Versa-Tether®	26
Using the Recline Bar	28
Using Child Seat Features	29
Securing Your Child	30
Harness Height Adjustment	32
Adjusting Buckle Position	33
Care and Maintenance	34
Warranty	38



WARNING!

DEATH or SERIOUS INJURY can occur if the following are not observed:

- Use this child seat forward-facing only.
- Use only with children who weigh between 22 and 80 pounds (10 and 36.3 kg) and whose height is 53 inches (134.6 cm) or less.
- Adjust the belts provided with this child seat so they fit snugly around your child. A snug strap should not allow any slack. It lies in a relatively straight line without sagging. It does not press on the child's flesh or push the child's body into an unnatural position.
- Secure the Versa-Tether® provided with this child seat.
- Secure this child seat with vehicle's Lower Anchors and Tethers for CHildren (LATCH) system if available or with a vehicle belt.
- Follow all instructions on this child seat and in the written instructions.
- Register your child seat with the manufacturer, Britax Child Safety, Inc. by visiting www.BritaxUSA.com/registration, OR complete and return the registration card that was shipped with this child seat.
- Refer to your vehicle owner's manual or contact the vehicle manufacturer for the maximum weight rating for their LATCH anchors. Use vehicle belt (not LATCH connectors) for installations with children who weigh more than the vehicle LATCH anchor limit. Unless specified otherwise by the vehicle manufacturer, assume a 40 pound (18.1 kg.) child is the vehicle LATCH anchor limit.
- The HUGS™ chest pads and the recline bar must be used at all times.
- This child seat must not be used in the home, in boats, or other non-certified applications.
- Secure this child seat even when it is not occupied. In a crash, an unsecured child seat may injure vehicle occupants.
- Never use the adjuster strap to lift or carry this child seat. Doing so could cause damage to the harness adjuster and webbing. Always carry this child seat by the shell or tether straps.
- Never route the vehicle belt over the child.
- Based on crash statistics, the National Highway Traffic Safety Administration (NHTSA) recommends that parents select the back seat as the safest location for a properly installed child seat. Please study [Vehicle Compatibility](#) on pages 10-11 to ensure your child's safety and consult your vehicle owner's manual.
- The primary protection for occupants of a vehicle in a collision is the body of the vehicle itself; a child seat will not protect a child when a vehicle is seriously impacted. However, correctly installed, a child seat will substantially improve chances for survival in most crashes. Make sure all users fully understand the correct ways to use this child seat in a vehicle.
- When using in vehicle with air bags, refer to the vehicle owner's manual for child seat installation instructions and precautions.
- To prevent injury due to deterioration or hidden damage, discontinue use of a child seat that is older than six years or has been in a moderate or severe crash. See date of manufacture located on the child seat.

IMPORTANT NOTES

- Verify that the child seat is secure and the harness is properly adjusted around the child each time the child seat is used.
- Adjust the harness to fit the clothes the child is wearing. Remove bulky coats and/or jackets before putting the child in the child seat.
- Cover the child seat when the vehicle is parked in direct sunlight. Parts of the child seat could become hot enough to burn a child.
- Store the child seat in a safe place when it is not being used. Avoid placing heavy objects on top of the child seat.
- Do not leave children alone in a vehicle, even for a short time.
- Do not, except as described in this booklet, attempt to disassemble any part of the child seat or change the way its harness or the vehicle's seat belts are used.
- Do not leave loose objects, e.g. books, bags, etc., in the back of a vehicle. In the event of a sudden stop, loose objects will keep moving, potentially causing serious injuries.
- Do not leave folding vehicle seats unlatched. In event of a sudden stop, a loose seat back could cause the child seat not to perform as intended.
- Do not allow children to play with this or any child seat.
- Do not use anything to raise the child seat off the vehicle seat except as described in these instructions. In a crash, this could cause the child seat not to perform as intended.

Certification

This child seat system conforms to all applicable Federal Motor Vehicle Safety Standards. **This child seat is NOT certified for use in aircraft.**

Registration

Child seats could be recalled for safety reasons. You must register this child seat to be reached in a recall. Send your name, address, and the child seat's model number and manufacturing date to Britax Child Safety, Inc., 13501 South Ridge Drive, Charlotte, NC 28273, or call 1-888-4BRITAX, or register online at www.BritaxUSA.com/ registration. For recall information, call the U.S. Government's Vehicle Safety Hotline at 1-888-327-4236 (TTY 1-800-424-9153), or go to <http://www.NHTSA.gov>.


According to the American Academy of Pediatrics: All infants should ride rear-facing until they have reached at least 1 year of age and weigh at least 20 pounds. That means that if your infant reaches 20 pounds before her first birthday, she should remain rear-facing at least until she turns 1 year old. It is best for children to ride rear-facing to the highest weight or height allowed by the manufacturer.

Forward-Facing

Weight 22 pounds (and 1 year) – 80 pounds (10 – 36.3 kg.)

Only use forward-facing with children:

- who are at least one year of age **and**
- who weigh between 22 and 80 lbs. (10 – 36.3 kg.) **and**
- who are 53" (134.6 cm.) or less in height **and**
- when the top of the child's ears are below the top of the child seat shell (Fig. A) **and**
- when the harness straps are located in the nearest slots at or above the child's shoulders.




IMPORTANT: See [Harness Height Adjustment](#) on page 32.



WARNING!

Do NOT use the child seat if **any** of the following apply:

- the child is less than one year of age **or**
- the child is less than 22 lbs. (10 kg.) in weight **or**
- the child exceeds 80 lbs. (36.3 kg.) in weight **or**
- the child exceeds 53" (134.6 cm.) in height **or**
- the top of the ears are above the top of the child seat shell (Fig. A) **or**
- the harness straps are in slots below the child's shoulders





- | | |
|--------------------|---|
| 1 Cover | 8 Buckle |
| 2 Harness Slots | 9 Belly Pad |
| 3 Harness | 10 Harness Release Lever (under flap) |
| 4 Harness Retainer | 11 LATCH Connectors |
| 5 Comfort Pads | 12 User Guide, Serial Number, and
Manufacture Date (under cover) |
| 6 Chest Clip | 13 Harness Adjuster Strap |
| 7 HUGS™ Chest Pads | |



- | | |
|---|-----------------------------------|
| 2 Shell | 19 LATCH Adjusters |
| 14 Versa-Tether® (Top Anchorage
Strap) | 20 LATCH Connector Release Button |
| 15 LATCH Storage Pouches (under
cover) | 21 Recline Bar |
| 16 Harness Yoke | 22 Storage Pouch |
| 17 LATCH Adjunster Release Buttons | |

Vehicle Safety Belts

NOTE: The information in this section only applies to installation with vehicle safety belts.



IMPORTANT: Vehicle seats and safety belts differ from vehicle to vehicle. Refer to your vehicle owner's manual for specific information about vehicle safety belts and their use with child seats. Some vehicles have no seating positions which are compatible with this child seat or any other child seat. If in doubt, contact the vehicle manufacturer for assistance.

This child seat can fit securely in most vehicles using existing vehicle belts. However, some vehicle designs prevent a secure fit of the child seat.

The vehicle owner's manual will have information on the types of vehicle belts in your vehicle. If your belt type is listed below, select another seating position or use **Lower Anchors and Tethers for Children (LATCH)**.



WARNING! The following types of vehicle belts are not compatible with this child seat:

- Front vehicle belts with top or bottom anchorage points in the door. (Fig. A & B)
- Motor-driven, automatic vehicle belts. (Fig. B)
- Lap-shoulder belts that have separate retractors for shoulder section and lap section in which lap section retractor does not lock.
- Non-locking, two-point Emergency Locking Retractor (ELR) vehicle belts without the use of a belt shortening clip.
- Lap-shoulder ELR vehicle belts without use of a locking clip.



Vehicle Seating Positions

WARNING! Forward-facing vehicle seats **MUST** be used with this child seat. Side-facing or rear-facing seats **CANNOT** be used. See diagram below.




WARNING! DO NOT place a child seat rear-facing in the front seat of a vehicle with a passenger air bag unless deactivated. DEATH or SERIOUS INJURY can occur. The back seat is the safest place for children under 12.

NOTE: Refer to your vehicle owner's manual to determine the kind of retractors used in your vehicle and how to operate them.

LATCH – Long Route

- Figure A illustrates a typical **Long Route LATCH** installation. The restraint is shipped with the LATCH strap and connectors in the long route configuration.
- If choosing to use LATCH verify that your vehicle is equipped with LATCH anchors. If LATCH anchors are not installed, you must use vehicle belt installation methods.



WARNING! Refer to your vehicle owner's manual or contact the vehicle manufacturer for the maximum weight rating for their LATCH anchors. Use vehicle belt (not LATCH connectors) for installations with children who weigh more than the vehicle LATCH anchor limit. Unless specified otherwise by the vehicle manufacturer, assume a 40 pound (18.1 kg) child is the vehicle LATCH anchor limit.

- 1 The recline bar must be used at all times with this seat. Insert the recline bar into the holes on the rear of the child seat. Use a rubber mallet to tap the recline bar ends into the holes. See page 28 for details.
- 2 Verify the LATCH strap is routed **under** the child seat cover in the long route configuration. (Fig. A)



NOTE: If you need to re-route the LATCH strap from the short route to the long route configuration:


- a Uninstall the child seat.
- b Loosen the harness and pull the top of the child seat cover away from the seat shell.
- c Pull each LATCH connector through the closet belt slot to the front of the child seat shell (Fig. B).

- d Press each LATCH adjuster release button and pull the webbing to fully extend the LATCH strap.
- e Route the child's left connector around to the outside of the seat shell.
- f Route the child's right LATCH connector through child's left belt slot from the front to the back of the child seat shell.
- g Route the child's right LATCH connector across the back of the child seat shell.
- h The LATCH strap must route **over** the harness straps on the rear of the child seat.
- i Route the child's right LATCH connector through the child's right belt slot to the front of the child seat.
- j Route the child's right connector around to the outside of the child seat shell.
- k Refit the child seat cover onto the child seat shell. Verify the LATCH strap is routed **under** the child seat cover.



- 3 Place the child seat sideways on the vehicle seat with the back of the child seat facing toward you.
 - 4 Loosen the Versa-Tether® and place it up and over the child seat back.
 - 5 If stored, remove the LATCH connectors from the LATCH storage pouches on the rear of the child seat.
 - 6 Verify that the LATCH strap is not twisted and attach the closest LATCH connector to the vehicle seat back to the farthest LATCH anchor (Fig. C)
 - The LATCH strap must be routed on the **outside** of recline bar.
 - The LATCH connector **MUST** be in an upright position (Fig. D).
 - A positive click confirms attachment.
- NOTE:** It may be necessary to switch the LATCH connectors if ANY of the following conditions exist:
- The LATCH connector is not in an upright position (Fig. D).
 - The LATCH strap is twisted.
 - A positive click is **NOT** heard when the LATCH connector and LATCH anchor are connected.

NOTE: If a positive click is not heard, but the LATCH connectors are in an upright position, you should not switch the LATCH connector. The strap may be too tight or twisted, or there may be debris in the LATCH connector.

- 7 Rotate the child seat into the forward-facing position. Ensure the bottom of the child seat shell is in full contact with the vehicle seat and the recline bar is resting against the vehicle seat back. 
- 8 Verify that the LATCH strap is routed **under** the child seat cover and is not twisted. Attach the remaining LATCH connector to the adjacent LATCH anchor. (Fig. E)
 - The LATCH strap must be routed on the **outside** of recline bar.
 - The LATCH connector **MUST** be in an upright position (Fig. F).
 - A positive click confirms attachment.
- 9 Alternately pull each LATCH strap loop while pushing the child seat firmly into the vehicle seat to evenly tighten the LATCH strap.
- 10 Attach the Versa-Tether® hook to the vehicle's designated tether anchor. Remove all slack from the tether to secure. See pages 26 – 27.
- 11 Store the excess webbing in a LATCH storage pouch on the back of the cover.
- 12 Verify that all connections are secure, the LATCH strap is tight and the child seat is secure.
 - The child seat is secure when it cannot be moved more than 1 inch front-to-back or side-to-side at the belt path. If the child seat is not secure, repeat this procedure or use an alternate seating position.




Lap-Shoulder Belt – Long Route

- Figure A illustrates a typical Long Route lap-shoulder belt installation.

IMPORTANT: Britax recommends that the Versa-Tether® be used at all times. Using the tether will improve the stability of the child seat and reduce the risk of injury. Check your vehicle owner's manual for approved tether locations.

- 1 The recline bar must be used at all times with this child seat. Insert the recline bar into the holes on the rear of the child seat. Use a rubber mallet to tap the recline bar ends into the holes. See page 28 for details.
- 2 If the vehicle is equipped with a designated tether anchor for the chosen seating position, remove the Versa-Tether® from the pouch, loosen and place it up and over the child seat back.
- 3 Place the child seat in the forward-facing position on the vehicle seat. Ensure the bottom of the child seat shell is in full contact with the vehicle seat and the recline bar is resting against the vehicle seat back.
- 4 Pull the vehicle belt out and route through the belt slot farthest from the vehicle buckle from the front to the rear of the child seat.
 - The vehicle belt must route **over** the child seat cover and **outside** of the recline bar.
- 5 Route the vehicle belt across the back of the child seat continuing through the belt slot closest to the vehicle buckle, to the front of the child seat shell (Fig. B).
 - The vehicle belt must be routed **over** the harness straps on the rear of the child seat.




- Route the vehicle belt around to the outside of the child seat near the vehicle buckle, routing **over** the child seat cover (Fig. B page 15).



- The vehicle belt must be routed on the **outside** of the recline bar.
- Verify that the vehicle belt is not twisted and then buckle (Fig. C).

- The shoulder portion of the vehicle belt must be routed **over** the front of the child seat (Fig. D).
- Push the child seat firmly into the vehicle seat while removing slack first from the lap portion and then the shoulder portion of the vehicle belt.



- Lock the vehicle belt according to the instructions in your vehicle owner's manual.

- Attach the Versa-Tether® hook to the designated tether anchor (if available according to the vehicle owner's manual) for the chosen seating position. Remove all slack from tether to secure. Store any excess webbing in a LATCH storage pouch on the back of the cover. See pages 26 – 27.


- Verify the vehicle belt is routed **over** the child seat cover.

- Verify that all connections are secure, the vehicle belt is tight and the child seat is stable.

- The child seat is secure when it cannot be moved more than 1 inch front-to-back or side-to-side at the belt path. If the child seat is not secure, repeat this procedure or use an alternate seating position.

Lap Belt – Long Route

- Figure A illustrates a typical Long Route lap belt installation.



IMPORTANT: Britax recommends that the Versa-Tether® be used at all times. Using the tether will improve the stability of the child seat and reduce the risk of injury. Check your vehicle owner's manual for approved tether locations.

- The recline bar must be used at all times with this child seat. Insert the recline bar into the holes on the rear of the child seat. Use a rubber mallet to tap the recline bar ends into the holes. See page 28 for details.
 - If the vehicle is equipped with a designated tether anchor for the chosen seating position, loosen the Versa-Tether® and place it up and over the child seat back.
 - Place the child seat in the forward-facing position on the vehicle seat. Ensure the bottom of the child seat shell is in full contact with the vehicle seat and the recline bar is resting against the vehicle seat back.
 - Pull the vehicle belt out and route **under** the child seat cover, around front of seat shell and through the belt slot furthest from the vehicle buckle, from the front to the rear of the child seat (Fig. B).
- The vehicle belt must be routed on the **outside** of the recline bar.
- Route the vehicle belt across the back of the child seat continuing through the belt slot closest to the vehicle buckle, from the rear to the front of the child seat shell.
- The vehicle belt must be routed **over** the harness straps on the rear of the child seat.



6 Route the vehicle belt **under** the child seat cover, around to the outside of the seat shell near the vehicle buckle (Fig. C).

- The vehicle belt must be routed on the **outside** of the recline bar.

7 Verify that the vehicle belt is not twisted and then buckle (Fig. D).

8 Push the child seat firmly into the vehicle seat while removing slack from the vehicle belt.

9 Lock the vehicle belt according to the instructions in your vehicle owner's manual.

10 Attach the Versa-Tether® hook to the designated tether anchor (if available according to the vehicle owner's manual) for the chosen seating position. Remove all slack from tether to secure. Store any excess webbing in a LATCH storage pouch on the back of the cover. See pages 26 – 27.


11 Verify that all connections are secure, the vehicle belt is tight and the child seat is stable.

- The child seat is secure when it cannot be moved more than 1 inch front-to-back or side-to-side at the belt path. If the child seat is not secure, repeat this procedure or use an alternate seating position.



LATCH – Short Route

- Figure A illustrates a typical **Short Route LATCH** installation. The restraint is shipped with the LATCH strap and connectors in the long route configuration.
- If choosing to use LATCH, verify that your vehicle is equipped with LATCH anchors. If LATCH anchors are not installed, you must use vehicle belt installation methods.



WARNING! The Versa-Tether must be used at all times in this mode of installation. Refer to your vehicle owner's manual or contact the vehicle manufacturer for the maximum weight rating for their LATCH anchors. Use vehicle belt (not LATCH connectors) for installations with children who weigh more than the vehicle LATCH anchor limit. Unless specified otherwise by the vehicle manufacturer, assume a 40 pound (18.1 kg) child is the vehicle LATCH anchor limit.

- 1 The recline bar must be used at all times with this child seat. Insert the recline bar into the holes on the rear of the child seat. Use a rubber mallet to tap the recline bar ends into the holes. See page 28 for details.
- 2 Verify the LATCH strap is routed **under** the child seat cover and the comfort foam in the short route configuration (Fig. A).



NOTE: If you need to re-route the LATCH strap from the long route to the short route configuration:

- a Uninstall the child seat.
- b Loosen the harness and pull the top of the child seat cover away from the seat shell.
- c Route the child's right LATCH connector through the child's right belt slot to the rear of the child seat shell continuing through the child's left belt slot to the front of child seat shell (Fig. B).

d Route the child's left LATCH connector through the child's left belt slot to the rear of the child seat.

e Route the child's right LATCH connector **under** the child seat cover, between the comfort foam and the child seat shell, then through the child's right belt slot to the rear of the child seat (Fig. C).

f Refit the child seat cover onto the child seat shell.

3 Place the child seat sideways on the vehicle seat with the back of the child seat facing you.

4 Loosen the Versa-Tether® and place it up and over the child seat back.

5 If stored, remove the LATCH connectors from storage pouches on the rear of the child seat.

6 Verify that the LATCH strap is not twisted and attach the closest LATCH connector to the vehicle seat back to the farthest LATCH anchor (Fig. D)



- The LATCH strap must be routed **inside** the recline bar. See page 28.
- The LATCH connector **MUST** be in an upright position (Fig. E).
- A positive click confirms attachment.

NOTE: It may be necessary to switch the LATCH connectors if ANY of the following conditions exist:

- The LATCH connector is not in an upright position (Fig. E).
- The LATCH strap is twisted.
- A positive click is NOT heard when the LATCH connector and LATCH anchor are connected.

NOTE: If a positive click is not heard, but the LATCH connectors are in an

upright position, you should not switch the LATCH connector. The strap may be too tight or twisted, or there may be debris in the LATCH connector.

7 Rotate the child seat into the forward-facing position. Ensure the bottom of the child seat shell is in full contact with the vehicle seat and the recline bar is resting against the vehicle seat back.

8 Verify that the LATCH strap is routed under the child seat cover and comfort foam and is not twisted. Attach the remaining LATCH connector to the adjacent LATCH anchor. (Fig. F)

- The LATCH strap must be routed **inside** the recline bar. See page 28.
- The LATCH connector **MUST** be in an upright position (Fig. E).
- A positive click confirms attachment.

9 Reach through the belt slots to access the loop ends of the LATCH connector strap (Fig. G).

10 Alternately pull each LATCH strap loop while pushing the child seat firmly into the vehicle seat to evenly tighten the LATCH strap.

11 Attach the Versa-Tether® hook to the vehicle's designated tether anchor. Remove all slack from the tether to secure. See pages 26 – 27.

12 Store the excess webbing in a LATCH storage pouch on the back of the cover.

13 Verify that all connections are secure, the LATCH strap is tight and the child seat is stable.

- The child seat is secure when it cannot be moved more than 1 inch front-to-back or side-to-side at the belt path. If the child seat is not secure, repeat this procedure or use an alternate seating position.





Lap-Shoulder Belt – Short Route

- Figure A illustrates a typical **Short Route** lap-shoulder belt installation.

WARNING! The Versa-Tether must be used at all times in this mode of installation. Check your vehicle owner's manual for designated tether anchor locations.

- 1 The recline bar must be used at all times with this child seat. Insert the recline bar into the holes on the rear of the child seat. Use a rubber mallet to tap the recline bar ends into the holes. See page 28 for details.
- 2 Loosen the Versa-Tether® and place it up and over the child seat back.
- 3 Place the child seat in the forward-facing position on the vehicle seat. Ensure the bottom of the child seat shell is in full contact with the vehicle seat and the recline bar is resting against the vehicle seat back.
- 4 Pull the vehicle belt out and route through the belt slot furthest from the vehicle buckle, from the rear to the front of the child seat (Fig. B).
 - The vehicle belt must be routed on the **outside** of the recline bar.




- 5 Route the vehicle belt **under** the child seat cover, between the comfort foam and the child seat shell, and through the belt slot closest to the vehicle buckle from front to rear of the child seat (Fig. C).

- The vehicle belt must be routed on the **outside** of the recline bar.

- 6 Verify that the vehicle belt is not twisted and then buckle (Fig D).
- 7 Push the child seat firmly into the vehicle seat while removing slack first from the lap portion and then the shoulder portion of the vehicle belt.

- 8 Lock the vehicle belt according to the instructions in your vehicle owner's manual.
- 9 Attach the Versa-Tether® hook to a tether anchor designated by the vehicle owner's manual for the chosen seating position. Remove all slack from tether to secure. Store any excess webbing in a LATCH storage pouch on the back of the cover. See pages 26 – 27.
- 10 Verify that all connections are secure, the vehicle belt is tight and the child seat is secure.

- The child seat is secure when it cannot be moved more than 1 inch front-to-back or side-to-side at the belt path. If the child seat is not secure, repeat this procedure or use an alternate seating position.





Lap Belt – Short Route

- Figure A illustrates a typical **Short Route** lap belt installation.

WARNING! Although Britax recommends that the Versa-Tether® be used at all times, the Versa-Tether must be used 50 – 80 lbs. in this mode of installation. Check your vehicle owner's manual for approved tether anchor locations.

- 1 The recline bar must be used at all times with this child seat. Insert the recline bar into the holes on the rear of the child seat. Use a rubber mallet to tap the recline bar ends into the holes. See page 28 for details.
- 2 Loosen the Versa-Tether® and place it up and over the child seat back.
- 3 Place the child seat in the forward-facing position on the vehicle seat. Ensure the bottom of the child seat shell is in full contact with the vehicle seat and the recline bar is resting against the vehicle seat back.
- 4 Pull the vehicle belt out and route through the belt slot furthest from the vehicle buckle, from the rear to the front of the child seat (Fig. B).
 - Vehicle belt must route on the **inside** of the recline bar.
- 5 Route the vehicle belt **under** the child seat cover, between comfort foam and the child seat shell, then through the belt slot closest to the vehicle buckle from front to rear of the child seat (Fig. C).
 - Vehicle belt must route on the **inside** of the recline bar.



- 6 Verify that the vehicle belt is not twisted and then buckle (Fig. D).
- 7 Push the child seat firmly into the vehicle seat while removing slack from the vehicle belt.
- 8 Lock the vehicle belt according to the instructions in your vehicle owner's manual.
- 9 Attach the Versa-Tether® hook to a tether anchor designated by the vehicle owner's manual for the chosen seating position. Remove all slack from tether to secure. Store any excess webbing in a LATCH storage pouch on the back of the cover. See pages 26 – 27.

- 10 Verify that all connections are secure, the vehicle belt is tight and the child seat is secure.
 - The child seat is secure when it cannot be moved more than 1 inch front-to-back or side-to-side at the belt path. If the child seat is not secure, repeat this procedure or use an alternate seating position.




WARNING!

- Attach the Versa-Tether only to tether anchors designated by your vehicle manufacturer as tether anchorage points. Use of other locations is not approved or permitted.
- Do NOT modify the vehicle without advice from the vehicle manufacturer if a tether anchor is not available.
- Do NOT hook the Versa-Tether to the bottom of a vehicle seat adjuster.
- Always use the Versa-Tether for children weighing more than 50 pounds (22.7 Kg).
- Always use the Versa-Tether when installed in the lap-shoulder short-route mode of installation.
- Britax® recommends that the tether be used at all times. Using the tether will improve the stability of your child seat and reduce the risk of injury.
- If your vehicle does not currently have a tether anchor attachment, refer to your vehicle owner's manual or contact your vehicle manufacturer for assistance.

Using the Versa-Tether

- 1 Consult your vehicle owner's manual for approved tether anchorage locations.
- 2 Locate the tether on the back of the child seat. Place the tether components up and over the child seat back.
- 3 Install the child seat using the LATCH system or the vehicle seat belts according to the instructions in this manual.
- 4 Lift the tether adjuster tab to release the tether straps, then pull to fully extend the tether into a "V" shape.
- 5 Locate the hook on the strap.
- 6 Hook the tether to the vehicle's designated anchor point (Fig. A).
- 7 Pull the tether adjuster belt to remove all slack.
- 8 Verify that there is tension in the tether strap and that the child seat is properly secured.
 - The child seat is secure when it cannot be moved front-to-back or side-to-side more than 1 inch (2.5 cm) at the belt path.



- The recline bar must be installed before using this restraint.
- 1 Insert the recline bar into the holes in lower rear of child seat prior to installation in vehicle (Fig. A).
 - 2 Use a rubber mallet to tap the recline bar ends into holes (Fig. A).
- Do not strike the center of the recline bar near the label as this may bend the recline bar.
- 3 Ensure that the bottom of the child seat shell is in full contact with the vehicle seat and the recline bar is resting against the vehicle seat back (Fig. B).




Belt Routing with the Recline Bar

The recline bar is provided to improve stability of the child seat. Proper installation is key to ensuring the best performance of the child seat.


Long Route Installation

When using the long route installation, the LATCH strap or vehicle belt strap must pass outside of the recline bar. (Fig. C)



Short Route Installation

When using the short route installation, the LATCH strap or vehicle belt strap must pass through the inside of the recline bar. (Fig. D)




EXCEPTION: When using the lap-shoulder belt however, the strap must pass on the **outside** of the recline bar.

Using the Chest Clip

Open the chest clip by squeezing the middle tabs, while pulling the two pieces apart (Fig. A).


IMPORTANT: The correct height for the chest clip is at the middle of the chest, level with the armpit.



Using the Buckle

Fastening the Buckle

- 1 Hold the buckle with one hand.
- 2 Use your other hand to insert one tongue at a time into the buckle. Proper connection is confirmed with a positive click, after inserting the second buckle tongue (Fig. B).



Releasing the Buckle


- 1 Hold the buckle with one hand.
- 2 Use thumb to press release button to eject the tongues from buckle (Fig. B).

NOTE: Periodically clean the buckle to ensure proper operation. See page 37.

Once the child seat has been installed in the vehicle, follow these instructions to secure your child in the child seat.

IMPORTANT: Before securing your child in the child seat, always check the adjuster area for debris (e.g., food, coins, toys, etc.). If debris is present, it must be removed to prevent interference with the adjuster mechanism.

- Loosen the harness by lifting the adjuster lever located in front of the child seat, then pull the shoulder straps forward (Fig. A).
- Open the chest clip by squeezing the middle tabs, while pulling the two pieces apart (Fig. B).
- Unfasten the buckle by pressing down on the middle button.
- Move the harness straps to the side of the child seat. To aid in holding the straps, insert the pieces of the chest clip into the harness retainers on the cover.
- Place the child in the child seat.
- Position the harness straps around the child and fasten the child seat buckle (Fig. C). Proper connection is confirmed with a positive click after inserting the second buckle tongue.
- Gently pull up on the harness straps to tighten the lap section of the harness, which should fit low on your child's body.
- Fasten the chest clip by connecting the two halves together (Fig. D).



- Slowly pull the adjuster strap to tighten the harness around the child (Fig. E).

- The correct height for the chest clip is at the middle of the chest, level with the child's armpit (Fig. F).
- The HUGS pads may be placed in any position that is comfortable for the child, within the range of the correctly placed chest clip.

- Verify that harness is not twisted and child is properly secured.

See [Safety Information](#) on pages 6 – 7.

WARNING! HUGS™ chest pads must be used at all times



IMPORTANT:

- Always pull on the harness after securing the child to ensure the buckle tongues are secure in the harness buckle. If the buckle will not fasten with a positive click after insertion of each buckle tongue, the harness buckle or adjuster area may be clogged with debris that needs to be removed. See page 37 for cleaning instructions.
- Adjust the belts provided with the child seat so they fit snugly around your child. A snug strap should not allow any slack. It lies in a relatively straight line without sagging. It does not press on the child's flesh or push the child's body into an unnatural position.

Harness Height Adjustment

- 1 Loosen the harness by lifting the harness release lever while pulling the shoulder straps forward as far as possible (Fig. A).
- 2 From the rear of the child seat, unhook the shoulder harness straps from the yoke (Fig. B).
- 3 Pull the harness straps through the shell, foam and cover to the front of the child seat.
- 4 Thread the harness straps through the appropriate harness slots in the cover, foam and seat shell. (Fig. C).
- 5 Reattach harness straps to the harness yoke.





 **WARNING!** HUGS™ chest pads must be used at all times.

- 6 Pull harness adjuster strap to tighten the harness.
- 7 Verify that all straps are threaded at the same height and are not twisted.

Adjusting Buckle Position

The buckle has two positions and should be adjusted to fit your child (Fig. A). Select the slot closest to, but not under, the child.



 **WARNING!** Do not use position two (2) until child exceeds 50 pounds (22.7 kg).

Remove the buckle, then rethread in appropriate position. See page 36 for buckle removal and rethreading instructions.

Cover Removal

WARNING! Do not take apart the harness. Never remove the buckle tongues from the harness. They cannot be reattached after removal. If reassembled incorrectly, the child seat may not perform as intended.

- 1 Loosen the harness by lifting the harness adjuster lever while pulling the shoulder straps forward as far as possible.
- 2 Unhook the shoulder straps from the harness yoke on the rear of the child seat (Fig. A).
- 3 Pull the upper harness straps through the shell and cover to the front of the child seat.
- 4 Remove the buckle and belly pad. See page 36.
- 5 Gently remove the upper portion of the cover. Be careful not to damage the energy-absorbing foam.
- 6 Pull the lower harness straps, buckle tongues, HUGS™ chest pads, and chest clip through the lower slots in cover.
- 7 Remove the entire cover from the child seat.



For additional demonstration please visit www.BritaxUSA.com.

Refitting the Cover

To refit the cover, reverse the above directions. Make sure that the shoulder straps are not twisted, and are threaded properly through the chest clips, cover, foam, and shell.

Cleaning the Cover

- HAND WASH using cold water and mild soap.
- LINE or LIE-FLAT DRY to prevent the cover from shrinking.
- **DO NOT** bleach, machine wash, machine dry or iron.

Cleaning the Shell

- SPONGE CLEAN using warm water and mild soap.
- TOWEL DRY
- **DO NOT** use solvents, abrasive cleaners or disassemble the harness.

Cleaning the Harness

- SPONGE CLEAN using warm water and mild soap.
- TOWEL DRY
- **DO NOT** bleach, machine wash, machine dry or disassemble the harness.


Cleaning the Harness Adjuster

Periodically check the adjuster area to be sure it is clean and free of food, drink or other debris. If debris is present, it must be removed to prevent interference with the adjuster mechanism.

- BRUSH AWAY LOOSE DEBRIS using a soft-bristled brush.
- SPONGE CLEAN using warm water and a mild soap.
- TOWEL DRY
- **DO NOT** use solvents, abrasive cleaners or disassemble the harness.

Buckle Removal

- 1 Locate the metal buckle strap retainer on the bottom of the child seat.
- 2 Pull retainer away from child seat to loosen.
- 3 Turn the retainer so that the short side will go through the slot in the child seat shell (Fig. A).
- 4 Push the retainer through slots in the shell and cover, to the front of the child seat.

**Rethreading the Buckle**

- 1 Locate the necessary buckle slot.
- 2 Turn the buckle retainer so that the short side will fit through the slot in the cover and child seat shell (Fig. A).
- 3 Push the retainer through the slots in the cover and shell to the bottom of the child seat.
- 4 Pull buckle away from the child seat until tight, then verify that the strap is not twisted and the release button is facing out.
- 5 Verify that the buckle retainer lies flat against the the child seat shell.



Cleaning the Buckle

If your child eats and drinks while in the child seat, you may need to check the buckle periodically and wash out any accumulated debris or dried liquids.

- THOROUGHLY RINSE, using warm water (Fig. B).
- SOAK, overnight if possible, using warm water to loosen hardened drinks or food.
- TEST THE BUCKLE, by fastening and unfastening until a positive click is heard after inserting the second buckle tongue (Fig. C). If click is not heard, repeat cleaning procedure.

TOWEL DRY**DO NOT:**

- Lubricate
- Use solvents
- Use soap or household detergents



This child seat was manufactured by Britax Child Safety, Inc. Britax® warrants this product to the original retail purchaser as follows:

LIMITED ONE-YEAR WARRANTY

This product is warranted against defective materials or workmanship for one year from the date of original purchase. Proof of purchase is required. The exclusive remedy for this warranty is that Britax will, at its option, provide repair or replacement components for this product or refund the original purchase price of the product. Britax reserves the right to discontinue or change fabrics, parts, models or products, or to make substitutions.

To make a claim under this warranty, contact Britax Consumer Services at 1-888-427-4829 or write to us using the address on the back cover of this booklet. Proof of purchase is required.

PLEASE COMPLETE AND MAIL THE OWNER REGISTRATION CARD WITHIN (30) DAYS OF PURCHASE OR VISIT WWW.BRITAXUSA.COM/REGISTRATION.

WARRANTY LIMITATIONS

This warranty does not include damages which arise from negligence, misuse or use not in accordance with the product instruction.

The use of non-Britax Child Safety, Inc. covers, inserts, toys, accessories, or tightening devices is not approved by Britax. Their use could cause this child seat to fail Federal Safety Standards or not perform as intended in a crash. Their use automatically voids the Britax warranty.

LIMITATION OF DAMAGES

The warranty and remedies as set forth above are exclusive and in lieu of all others, oral or written, express or implied. In no event will Britax, or the retailer selling this product, be liable for any damages, including incidental or consequential damages, arising out of the use or inability to use this product.

LIMITATIONS OF WARRANTIES AND OTHER WARRANTY TERMS AND STATE LAWS

Any implied warranties, including implied warranties of merchantability and fitness for a particular purpose, shall be limited to the duration and terms of the express written warranty. Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply. This warranty gives you specific legal rights, and you may have other rights, which vary from state to state. Neither Britax, nor the retailer selling this product, authorizes any person to create for it any other warranty, obligation, or liability in connection with this product.

Britax
Childcare



First class travel for children

Britax Child Safety, Inc.
13501 South Ridge Drive
Charlotte, NC 28273
USA

A **Britax Childcare** company

Tel: 1-888-4BRITAX

BritaxUSA.com